



Product quality		
<b>Formats</b>		1209 x 225 x 5,3 mm
<b>Packaging</b>	<b>Pack:</b>	8 elements / 2,493 m <sup>2</sup> / 19,66 kg
	<b>Pallet:</b>	42 packs / 91,4 m <sup>2</sup> / 840,7 kg








Tolerances (Requirement EN 16511:2014)		
<b>Squareness of the elements (≤ 0.50mm)</b>		≤ 0,20 mm
<b>Determination of Linearity (≤ 0.30 mm/m)</b>		≤ 0,30 mm/m
<b>Flatness concave / convex</b>	<b>lengthwise (≤ 0.50/≤ 1.0 %)</b>	≤ 0,50/≤ 1,0 %
	<b>wide (≤ 0.10/≤ 0.15 %)</b>	≤ 0,15/≤ 0,20 %
<b>Surface flushness</b>	<b>(average ≤ 0.15 mm)</b>	(average ≤ 0.10 mm)
	<b>(max. ≤ 0.20 mm)</b>	(max. ≤ 0.15 mm)
<b>Opening between installed elements</b>	<b>(average ≤ 0.15 mm)</b>	(average ≤ 0.15 mm)
	<b>(max. ≤ 0.20 mm)</b>	(max. ≤ 0.20 mm)

Guarantee (according Parador guarantee conditions)		Notes
Domestic area	Commercial area	- not suitable for all-over adhesion
10 Years	-	- cleaning and maintenance see instructions
		- technical changes reserved



EN 14041:2004/AC:2006



Classification			
		Test method	Rating
	<b>Utility class 23</b> domestic areas with intensive use	EN 16511	Living room, hall, kitchen, home office
	<b>Utility class 31</b> commercial areas with low use	EN 16511	Hotels, small offices
	Reaction to fire	EN 13501-1	B <sub>fl</sub> -s1
	Slip resistance	EN 13893 EN 14041	μ ≥ 0,30 DS
	Light fastness	EN ISO 105 - B02	Blue wool scale: Stage ≥ 6
	Indentation-residual	EN ISO 24343-1	≤ 0,05 mm
	Formaldehyde emission (E1 = 0.1 ppm)	ISO 16000	< E1
	Dimensional stability	EN 16511	≤ 0,25 %
	Disposal	EAK-Code-number	20 03 38

Provisional Data Sheet - Errors and technical changes excepted.

Changed:	QMB Parador	File:	20190225_PA_TDS_Basic_5.3_EN
Date:	15.12.2018	Latest update at:	<a href="http://www.parador.eu/service/catalogues-downloads/technical-data-sheets">www.parador.eu/service/catalogues-downloads/technical-data-sheets</a>